

SPECIFICATIONS

	MODEL	SZ19-36	SZ22-48	SZ26-52
Engine	Manufacturer	Kawasaki		
	Model Number	FX600V	FX691V	FT730V-EFI
	Max Engine Power [HP]*	19	22	26
	Type	Gasoline, Air-Cooled V-Twin		
	Engine Displacement [cu. in. (cc)]	36.8 (603)	44.3 (726)	
Traveling System	Fuel Tank [gal. (L)]	5.1 (19.3)	6.5 (24.6)	
	Transmission	Hydro-Gear ZT3100	Hydro-Gear ZT3400	Hydro-Gear ZT3600
	Front Tires	11 x 4.0-5 (Flat-Free)	13 x 5.0-6 (Flat-Free)	
	Rear Tires	20 x 8-10	23 x 8.5-12	23 x 10.5-12
	Traveling Speed - Fwd [mph (km/h)]	9 (14.4)	10.5 (16.9)	11 (17.7)
	Traveling Speed - Rev [mph (km/h)]	4 (6.4)		
	Parking Brake	Cog Style Parking Lock / Hand Lever		
Mower	Cutting Width [in. (mm)]	36 (914.4)	48 (1219.2)	52 (1320.8)
	Cutting Height [in. (mm)]	1.5-4.5 (38.1-114.3)		
	Deck Depth [in. (mm)]	4.75 (120.65)		
	Blade Tip Speed (max) [FPM]	17,600	18,000	18,450
	Mounting Method	Parallel Linkage		
	Adjustment of Cutting Height	Pin		
	Number of Blades	2	3	
Dimensions	Overall Length [in. (mm)]	62.5 (1587.5)	63.75 (1619.25)	
	Overall Width w/ Mower [in. (mm)]	35.5 (901.7)	48.375 (1228.725)	53.875 (1368.425)
	Overall Height [in. (mm)]	45 (1143)	45.75 (1162.05)	
	Wheelbase [in. (mm)]	47.25 (1200.15)	46 (1168.4)	
	Min. Ground Clearance [in. (mm)]	2.75 (69.85)	4.25 (107.95)	
	Weight w/ Mower Deck [lbs. (kg)]	831 (376.9)	965 (437.7)	997 (452.2)
PTO	Drive System	Belt		
	Clutch Type	Electric		

*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.